

CLAIM AMENDMENTS

IN THE CLAIMS

This listing of the claims will replace all prior versions, and listing, of claims in the application or previous response to office action:

- 1-7. (Canceled)
- 8. (Canceled)
- 9. (Canceled)
- 10. (Canceled)
- 11. (Canceled)
- 12. (Canceled)
- 13. (Canceled)

14. (Previously Presented) A system for device registration replication in a packet-based network, comprising:

a first call manager and a second call manager coupled to the packet-based network, the first and second call managers each controlling one or more devices and storing composite registration information associated with the devices controlled by the first and second call managers;

the first call manager operable to:

determine that the second call manager has come on-line and communicate local registration information associated with the devices controlled by the first call manager to the second call manager;

communicate registration information associated with a newly registered device controlled by the first call manager to the second call manager;

communicate a deletion message to the second call manager indicating the removal of a device from the control of the first call manager; and

determine that the second call manager has gone off-line and delete registration information associated with devices controlled by the second call manager from the composite registration information stored by the first call manager.

15-53. (Canceled)

54. (Currently Amended) A method for device registration replication, comprising:
providing a plurality of call managers in a packet-based network, each call manager controlling one or more devices coupled to the packet-based network and storing composite registration information associated with the devices, wherein the composite registration information comprises a telephone number associated with at least one device and a process identification string identifying a device process executing in a call manager controlling the at least one device, the device process coordinating communication with the at least one device;

communicating status information from a first call manager to a second call manager in response to a change in which call manager of the plurality of call managers controls a device;
and

updating the composite registration information stored by the second call manager in response to receiving the status information.

55. (Previously Presented) The method of Claim 54, wherein:
communicating status information in response to a change in the control status of a device comprises communicating registration information associated with a newly registered device controlled by the first call manager; and

updating the composite registration information comprises adding the registration information associated with the newly registered device to the composite registration information stored by the second call manager.

56. (Previously Presented) The method of Claim 54, wherein:
communicating status information in response to a change in the control status of a device comprises communicating a deletion message indicating the removal of a device from the control of the first call manager; and

updating the composite registration information comprises deleting the registration information associated with the device from the composite registration information stored by the second call manager.

57. (Previously Presented) The method of Claim 56, further comprising determining that a device has been removed from the control of the first call manager in response to a failure by the first call manager to receive a response from the device to a polling message transmitted to the device by the first call manager.

58. (Previously Presented) The method of Claim 54, wherein the composite registration information comprises:

local registration information associated with devices controlled by the second call manager storing the composite registration information; and

remote registration information associated with devices controlled by other call managers.

59. **(Canceled)**

60. (Previously Presented) The method of Claim 54, wherein the composite registration information is stored in a registration information table.

61. **(Currently Amended)** A system for device registration replication in a packet-based network comprising a plurality of call managers, the system comprising:

a first call manager and a second call manager coupled to the packet-based network, the first and second call managers each controlling one or more devices and storing composite registration information associated with the devices, **wherein the composite registration information stored in the first and second call managers comprises a telephone number associated with at least one device and a process identification string identifying a device process executing in the call manager controlling the at least one device, the device process coordinating communication with the at least one device;**

the first call manager operable to communicate status information to the second call manager in response to a change in which call manager of the plurality of call managers controls a device; and

the second call manager operable to update the composite registration information stored by the second call manager in response to receiving status information from the first call manager.

62. **(Previously Presented)** The system of Claim 61, wherein:

the first call manager is operable to communicate status information in response to a change in the control status of a device by communicating registration information associated with a newly registered device controlled by the first call manager; and

the second call manager is operable to update the composite registration information stored the second call manager by adding the registration information associated with the newly registered device to the composite registration information stored by the second call manager.

63. (Previously Presented) The system of Claim 61, wherein:
the first call manager is operable to communicate status information in response to a change in the control status of a device by communicating a deletion message indicating the removal of a device from the control of the first call manager; and

the second call manager is operable to update the composite registration information stored by the second call manager by deleting the registration information associated with the device from the composite registration information stored by the second call manager.

64. (Previously Presented) The method of Claim 63, wherein the first call manager is further operable to determine that a device has been removed from the control of the first call manager in response to a failure by the first call manager to receive a response from the device to a polling message transmitted to the device by the first call manager.

65. (Previously Presented) The system of Claim 61, wherein the composite registration information stored in the second call manager comprises:

local registration information associated with devices controlled by the second call manager; and

remote registration information associated with devices controlled by the first call manager.

66. (Canceled)

67. (Currently Amended) The system of Claim ~~[[66]]~~ 61, wherein each telephone number is associated with a process identification string in a registration information table.

68. (Previously Presented) The system of Claim 61, wherein the first call manager is further operable to:

- determine that the second call manager has gone off-line; and
- delete registration information associated with devices controlled by the second call manager from the composite registration information stored by the first call manager.

69. (Previously Presented) The system of Claim 68, wherein the first call manager determines that the second call manager has gone off-line when the first call manager fails to receive a response to a polling message sent to the second call manager, the second call manager having previously responded to a polling message from the first call manager.

70. (Previously Presented) The system of Claim 61, wherein the first call manager is further operable to:

- determine that the second call manager has come on-line; and
- communicate local registration information associated with devices controlled by the first call manager to the second call manager.

71. (Previously Presented) The system of Claim 70, wherein the first call manager determines that the second call manager has come on-line when the first call manager receives a response to a polling message from the second call manager indicating that the second call manager is on-line.

72. (Previously Presented) The system of Claim 71, further comprising a third call manager operable to:

- determine that the second call manager has come on-line; and
- communicate local registration information associated with devices controlled by the third call manager to the second call manager.

73. (Previously Presented) The system of Claim 72, wherein the second call manager is further operable to combine the registration information received from the first and third call managers to form the composite registration information stored by the second call manager.

74. (Previously Presented) The system of Claim 73, wherein the second call manager is further operable to add local registration information associated with devices controlled by the second call manager to the composite registration information stored by the second call manager.

75. (Withdrawn) A first call manager coupled to a packet-based network that comprises a plurality of call managers, the first call manager comprising:

one or more device processes controlling one or more devices coupled to the packet-based network; and

a digit analysis module storing composite registration information associated with the devices;

the first call manager operable to communicate status information from the digit analysis module to a second call manager in response to a change in which call manager of the plurality of call managers controls one of the devices.

76. (Withdrawn) The first call manager of Claim 75, wherein the digit analysis module is operable to communicate status information in response to a change in the control status of a device by communicating registration information associated with a newly registered device controlled by the first call manager.

77. (Withdrawn) The first call manager of Claim 75, wherein the digit analysis module is operable to communicate status information in response to a change in the control status of a device by communicating a deletion message indicating the removal of a device from the control of the first call manager.

78. (Withdrawn) The first call manager of Claim 77, further operable to determine that a device has been removed from the control of the first call manager in response to a failure by the first call manager to receive a response from the device to a polling message.

79. (Withdrawn) The first call manager of Claim 75, wherein the digit analysis module is operable to communicate status information directly to a digit analysis module of the second call manager.

80. (Withdrawn) The first call manager of Claim 75, further operable to:
determine that a second call manager has gone off-line; and
delete registration information associated with devices controlled by the second call manager from the composite registration information stored in the digit analysis module of the first call manager.

81. (Withdrawn) The first call manager of Claim 80, wherein the first call manager determines that the second call manager has gone off-line when the first call manager fails to receive a response to a polling message sent to the second call manager, the second call manager having previously responded to a polling message from the first call manager.

82. (Withdrawn) The first call manager of Claim 75, further operable to:
determine that a second call manager has come on-line; and
communicate local registration information associated with devices controlled by the first call manager to the second call manager.

83. (Withdrawn) The first call manager of Claim 82, wherein the first call manager determines that the second call manager has come on-line when the first call manager receives a communication from the second call manager indicating that the second call manager is on-line.

84. (Withdrawn) First call manager software embodied in a computer-readable medium and operable to perform the following steps when executed by a computer:

control one or more devices coupled to a packet-based network;

store registration information associated with the devices controlled by the first call manager software; and

communicate status information to second call manager software in response to a change in which call manager controls a device.

85. (Withdrawn) The first call manager software of Claim 84, further operable to communicate status information in response to a change in the control status of a device by communicating registration information associated with a newly registered device controlled by the first call manager software.

86. (Withdrawn) The first call manager software of Claim 84, further operable to communicate status information in response to a change in the control status of a device by communicating a deletion message indicating the removal of a device from the control of the first call manager software.

87. (Withdrawn) The call manager software of Claim 86, further operable to determine that a device has been removed from the control of the first call manager software in response to a failure to receive a response from the device to a polling message.

88. (Withdrawn) The first call manager software of Claim 84, further operable to:
store registration information associated with devices controlled by the second call manager software;

determine that the second call manager software has gone off-line; and

delete registration information associated with the devices controlled by the second call manager software.

89. (Withdrawn) The first call manager software of Claim 88, further operable to determine that the second call manager has gone off-line in response to the first call manager software failing to receive a response to a polling message sent to the second call manager software.

90. (Withdrawn) The first call manager software of Claim 84, further operable to:
determine that the second call manager software has come on-line; and
communicate local registration information associated with devices controlled by the first call manager software to the second call manager software.

91. (Withdrawn) The first call manager software of Claim 90, further operable to determine that the second call manager has come on-line when the first call manager software receives a communication from the second call manager software indicating that the second call manager software is on-line.

92. (Withdrawn) A first call manager coupled to a packet-based network comprising a plurality of call managers, the first call manager comprising:
means for controlling one or more devices coupled to the packet-based network; and
means for storing composite registration information associated with the devices;
means for communicating status information to a second call manager in response to a change in which call manager of the plurality of call managers controls a device.

93. (Withdrawn) The first call manager of Claim 92, further comprising means for communicating registration information associated with a newly registered device controlled by the first call manager.

94. (Withdrawn) The first call manager of Claim 92, further comprising means for communicating a deletion message indicating the removal of a device from the control of the first call manager.

95. (Withdrawn) The first call manager of Claim 94, further comprising means for determining that a device has been removed from the control of the first call manager in response to a failure by the first call manager to receive a response from the device to a polling message.

96. (Withdrawn) The first call manager of Claim 92, further comprising:
means for determining that a second call manager has gone off-line; and
means for deleting registration information associated with devices controlled by the second call manager from the composite registration information stored by the first call manager.

97. (Withdrawn) The first call manager of Claim 96, further comprising means for determining that the second call manager has gone off-line when the first call manager fails to receive a response to a polling message sent to the second call manager, the second call manager having previously responded to a polling message from the first call manager.

98. (Withdrawn) The first call manager of Claim 92, further comprising:
means for determining that a second call manager has come on-line; and
means for communicating local registration information associated with devices controlled by the first call manager to the second call manager.

99. (Withdrawn) The first call manager of Claim 98, further comprising means for determining that the second call manager has come on-line when the first call manager receives a communication from the second call manager indicating that the second call manager is on-line.